

	ECC 300.2	ECC 600.2	ECC 500.4	ECC 600.4	ECC 1200.1D	PA 560.2	PA 1600.2	PA 800.4
Kanäle Channels	2	2	4	4	1	2	2	4
Ausgangsleistung (RMS) Output Power (RMS)	@14,4V/ 1%THD	@14,4V/ 1%THD	@14,4V/ 1%THD	@14,4V/ 1%THD	@14,4V/ 1%THD	@12,6V/ 1%THD	@12,6V/ 1%THD	@12,6V/ 1%THD
Stereo 1 Ohm					1 x 1135 W			
Stereo 4 Ohm	2 x 130 W	2 x 280 W	2x75 + 2x145 W	4 x 130 W	1 x 410 W	2 x 92 W	2 x 307 W	4 x 154 W
Stereo 2 Ohm	2 x 225 W	2 x 480 W	2x115 + 2x230 W	4 x 210 W	1 x 730 W	2 x 171 W	2 x 570 W	4 x 286 W
Gebrückt (bridged) 4 Ohm	1 x 455 W	1 x 955 W	1x235 + 1x440 W	2 x 410 W	1 x 2300 W	1 x 342 W	1 x 1174 W	2 x 572 W
Gebrückt (bridged) 2 Ohm								
T.H.D. T.H.D.	< 0.02 %	< 0.02 %	< 0.02 %	< 0.02 %	< 0.5 %	< 0.03	< 0.03 %	< 0.05 %
Frequenzgang Frequency Response	10 Hz - 30 kHz	10 Hz - 30 kHz	10 Hz - 30 kHz	10 Hz - 30 kHz	10 Hz - 30 kHz	5 Hz - 150 kHz	5 Hz - 150 kHz	10 Hz - 50 kHz
Signal/Rauschabstand S/N Ratio:	> 92 dB	> 96 dB	> 92 dB	> 92 dB	> 92 dB	> 100 dB	> 100 dB	> 100 dB
Eingangsempfindlichkeit Input Sensitivity	100 mV - 7 V	100 mV - 7 V	100 mV - 7 V	100 mV - 7 V	100 mV - 7 V	0.4 V - 8 V	0.4 V - 8 V	0.4 V - 8 V
Subsonic Filter schalt/regelbar Subsonic filter scolded/adjustable		•	•	•		•	•	
High Level in High Level in	•	•	•	•		•	•	•
Remote Level Control Remote Level Control		•			•	•	•	•
Frequenzweiche Eingang x-over	HP; 50 - 500 Hz switchable to 500 - 5000 Hz switchable 12 dB/ Octave	HP; 50 - 500 Hz switchable to 500 - 5000 Hz switchable 12 dB/ Octave	HP; 50 - 500 Hz switchable to 500 - 5000 Hz switchable 12 dB/ Octave	HP; 50 - 500 Hz switchable to 500 - 5000 Hz switchable 12 dB/ Octave	HP; 50 - 500 Hz switchable to 500 - 5000 Hz switchable 12 dB/ Octave	HP; 20 - 200 Hz switchable to 400 - 4000 Hz switchable 12 dB/ Octave LP; 40 - 400 Hz switchable to 800 - 8000 Hz	HP; 20 - 200 Hz switchable to 400 - 4000 Hz switchable 12 dB/ Octave LP; 40 - 400 Hz switchable to 800 - 8000 Hz	Front HP; 20 - 200 Hz switchable to 400 - 4000 Hz 40 - 4000 Hz Rear 20 - 200 Hz switchable to 400 - 4000 Hz 40 - 4000 Hz Front LP; 40 - 400 Hz switchable to 800 - 8000 Hz Rear 40 - 400 Hz switchable to 800 - 8000 Hz
Maße: L x B x H mm Diemensions	310x248x57.5	500x248x57.5	400x248x57.5	500x248x57.5	400x248x57.5	280x270x50	450x270x50	450x270x50