

	<b>ECC 300.2</b>	<b>ECC 600.2</b>	<b>ECC 500.4</b>	<b>ECC 600.4</b>	<b>ECC 1200.1D</b>	<b>PA 560.2</b>	<b>PA 1600.2</b>	<b>PA 800.4</b>
<b>Kanäle</b> Channels	2	2	4	4	1	2	2	4
<b>Ausgangsleistung (RMS)</b> Output Power (RMS)	@14,4V/ 1%THD	@14,4V/ 1%THD	@14,4V/ 1%THD	@14,4V/ 1%THD	@14,4V/ 1%THD	@12,6V/ 1%THD	@12,6V/ 1%THD	@12,6V/ 1%THD
<b>Stereo 1 Ohm</b>					1 x 1135 W			
<b>Stereo 4 Ohm</b>	2 x 130 W	2 x 280 W	2x75 + 2x145 W	4 x 130 W	1 x 410 W	2 x 92 W	2 x 307 W	4 x 154 W
<b>Stereo 2 Ohm</b>	2 x 225 W	2 x 480 W	2x115 + 2x230 W	4 x 210 W	1 x 730 W	2 x 171 W	2 x 570 W	4 x 286 W
<b>Gebrückt (bridged) 4 Ohm</b>	1 x 455 W	1 x 955 W	1x235 + 1x440 W	2 x 410 W	1 x 2300 W	1 x 342 W	1 x 1174 W	2 x 572 W
<b>Gebrückt (bridged) 2 Ohm</b>								
<b>T.H.D.</b> T.H.D.	< 0.02 %	< 0.02 %	< 0.02 %	< 0.02 %	< 0.5 %	< 0.03	< 0.03 %	< 0.05 %
<b>Frequenzgang</b> Frequency Response	10 Hz - 30 kHz	10 Hz - 30 kHz	10 Hz - 30 kHz	10 Hz - 30 kHz	10 Hz - 30 kHz	5 Hz - 150 kHz	5 Hz - 150 kHz	10 Hz - 50 kHz
<b>Signal/Rauschabstand</b> S/N Ratio:	> 92 dB	> 96 dB	> 92 dB	> 92 dB	> 92 dB	> 100 dB	> 100 dB	> 100 dB
<b>Eingangsempfindlichkeit</b> Input Sensitivity	100 mV - 7 V	100 mV - 7 V	100 mV - 7 V	100 mV - 7 V	100 mV - 7 V	0.4 V - 8 V	0.4 V - 8 V	0.4 V - 8 V
<b>Subsonic Filter schalt/regelbar</b> Subsonic filter scolded/adjustable		•	•	•		•	•	
<b>High Level in</b> High Level in	•	•	•	•		•	•	•
<b>Remote Level Control</b> Remote Level Control		•			•	•	•	•
<b>Frequenzweiche Eingang</b> x-over	HP; 50 - 500 Hz switchable to 500 - 5000 Hz switchable 12 dB/ Octave	HP; 50 - 500 Hz switchable to 500 - 5000 Hz switchable 12 dB/ Octave	HP; 50 - 500 Hz switchable to 500 - 5000 Hz switchable 12 dB/ Octave	HP; 50 - 500 Hz switchable to 500 - 5000 Hz switchable 12 dB/ Octave	HP; 50 - 500 Hz switchable to 500 - 5000 Hz switchable 12 dB/ Octave	HP; 20 - 200 Hz switchable to 400 - 4000 Hz switchable 12 dB/ Octave  LP; 40 - 400 Hz switchable to 800 - 8000 Hz	HP; 20 - 200 Hz switchable to 400 - 4000 Hz switchable 12 dB/ Octave  LP; 40 - 400 Hz switchable to 800 - 8000 Hz	<b>Front</b> HP; 20 - 200 Hz switchable to 400 - 4000 Hz 40 - 4000 Hz <b>Rear</b> 20 - 200 Hz switchable to 400 - 4000 Hz 40 - 4000 Hz ..... <b>Front</b> LP; 40 - 400 Hz switchable to 800 - 8000 Hz <b>Rear</b> 40 - 400 Hz switchable to 800 - 8000 Hz
<b>Maße: L x B x H mm</b> Diemensions	310x248x57.5	500x248x57.5	400x248x57.5	500x248x57.5	400x248x57.5	280x270x50	450x270x50	450x270x50